LTR28 Series 433MHz/868MHz MP(+20dBm) RF LoRa Transceiver Modules

Features - Radio

- 433MHz/868MHz ISM Frequency Band, LoRa and (G)FSK modem, SX1262 IC
- Data rate – Up to 300kbps for (G)FSK, Up to 62.5kbps for LoRa
- -146dBm Receiver Sensitivity (LoRa, SF-12, BW-10.4kHz)
- +20dBm RF Output Power (adjustable with 1dB step size)
- Buffer packet data, spectrum shaping, FEC-Forward Error Correction
- Low current consumption, 4.9mA in receive mode, 600nA in sleep mode
- Full radio configuration/control and modem/data parameters

Other

- Power Supply : 1.8V~3.6V
- Operating Temperature : -40°C~+85°C
- Small profile : 32.49mmx23.64mm (LTR28RSH8/LTR28RSH4)

  27.73mmx23.64mm (LTR28CSH8/LTR28CSH4)

  23.41mmx19.58mm (LTR28-S8/LTR28-S4)

  27.73mmx19.58mm (LTR28-SC8/LTR28-SC4)

MPN	Frequency	Connector	RF Shield
LTR28RSH8	868MHz	SMA RF Connector	Yes
LTR28RSH4	433MHz	SMA RF Connector	Yes
LTR28CSH8	868MHz	U.FL RF Connector	Yes
LTR28CSH4	433MHz	U.FL RF Connector	Yes
LTR28-S8	868MHz	SMD/RF Pin	Yes
LTR28-S4	433MHz	SMD/RF Pin	Yes
LTR28-SC8	868MHz	SMD/U.FL RF Connector	Yes
LTR28-SC4	433MHz	SMD/U.FL RF Connector	Yes









EGN Elektronik